

# MATERIAL SAFETY DATA SHEET

The information contained within this MSDS details health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user of this product should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Gripset Industries Pty Ltd. Gripset Industries Pty Ltd makes no representation as to the completeness and accuracy of the data contained in this data sheet. It is the user's obligation to evaluate and use this product safely, and to comply with all relevant Federal, State and Local Government laws and regulations. Gripset Industries Pty Ltd shall not be responsible for loss, damage or injury resulting from reliance upon or failure to adhere to any recommendation or information contained herein, from abnormal use of the material, or any hazard inherent in the nature of the material.

## STATEMENT OF HAZARDOUS NATURE

**Not classified as hazardous according to criteria of Worksafe Australia.**

## COMPANY DETAILS

Company	: Gripset Industries Pty Ltd A.C.N. 137 930 093
Address	: 30-32 Park Avenue, Woodville North SA 5012, Australia
Telephone numbers	: +61 (8) 8124-7300 or 1800 650 435
Facsimile number	: +61 (8) 8124-7350

## IDENTIFICATION

Product Name	: <b>Elastoproof</b>
Other Names	: B50, B10, CN90, CN270, CL- Blind, Joint Section +, L, T
Chemical Name	: NBR – Nitrile Butadiene Rubber – Cured
Manufacturer's Product Code	: Elastoproof
UN Number	: None assigned
Dangerous Goods Class	: None assigned
Subsidiary Risk	: None assigned
Shipping Name	: None assigned
Hazchem Code	: None assigned
Poisons Schedule Number	: None assigned

### Use

Major recommended uses	: Waterproof Detailing System
------------------------	-------------------------------

### Physical Description / Properties

Appearance	: Rubber solid, Grey
Boiling Point (°C)	: N/A
Specific Gravity	: 1.2
Flashpoint (°C)	: Not Applicable
Flammability Limits	: Not Applicable
Solubility in Water	: Insoluble

### Other Properties

Vapour Density	: N/A
Form	: Solid Rubber
Stability	: Considered Stable
Hazardous Polymerisation	: Will not occur
Materials to avoid	: Strong oxidising agents and bases, extreme heat.

### Ingredients

Chemical Name:	CAS Number:	Proportion:
NBR – Nitrile Butadiene Rubber – cured	-	100%

# MATERIAL SAFETY DATA SHEET

## HEALTH HAZARD INFORMATION

Swallowed	: Seek medical attention
Eye	: Rinse with water for a few minutes
Skin	: May cause skin irritation. Wash with water and soap.
Inhaled	: This material in the cured form precludes inhalation

## PRECAUTIONS FOR USE

**Threshold Exposure Limits** Not established

### Personal Protection

Respirator Type (AS/NZS 1716)	: N/A
Skin protection	: N/A
Eye protection	: N/A
Clothing	: N/A

## SAFE HANDLING INFORMATION

**Storage & Transport** N/A

### Spills & Disposal

Clean Up Spills / Leaks	: N/A
Disposal	: Dispose of in accordance with Local, State and Federal regulations.
Precautions for Clean Up Crew	: N/A

### Fire / Explosion Hazard

Flammability	: May be combustible at high temperatures
Flash Point	: Not determined
Fire/Explosion Hazards	: N/A
List of Dangerous Decomposition or Combustion Products	: Carbon oxides, sulphur oxides and various hydrocarbons.
Types of Extinguisher	: Water, Foam, CO <sub>2</sub> and Dry Chemical.
Precautions	: None. Not an explosion hazard
Protective Clothing	: Self-contained breathing apparatus
Reactivity	: None, product is not reactive

## OTHER INFORMATION

Ecology	: Avoid contaminating waterways and sewers.
Packaging & Labelling	: Various

## CONTACT POINT

Gripset Technical Department	: +61 (8) 8124-7300 or 1800 650 435	<b>Distributor Cyprus: M. A. Total Build Ltd</b>
Australia Poisons Information Centre	: 13 11 26	149 Arch. Makarios III Avenue, 3021 Limassol,
Police & Fire Brigade:	: 000	Cyprus, Email: info@totalbuild.com.cy
		Tel: +357 99 121841, Fax: +357 25 381403

