

MATERIAL SAFETY DATA SHEET



Page 1 of 3

EVO-BOND

SECTION I - IDENTIFICATION:

Chemical Name: *EVO-BOND* - Dated: July 2017

Product description : 100% Acrylic emulsion

Distributor : M. A. Total Build Ltd

SECTION II - INGREDIENTS:

COMPONENT INFORMATION

Acrylic Polymers non hazardous 46 - 48 % concentration

Residual Monomers non hazardous < 0.05%

Water

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS:

Apperance/Odour - liquid / acrylic

State liquid

Vapor Density 17.0 mmHg at 20C.

Solubility in Water - dilutable

Boiling Point 100C.

Specific Gravity 10 - 60 mPa.s

Evaporation Rate - < 1 water

pH 8.0 pH

Storage 49° C

SECTION IV - FIRE & EXPLOSION HAZARD DATA:

FIRE & EXPLOSIVE PROPERTIES:

FLASH POINT Non Combustible **METHOD USED:** N/A

FLAMMABLE LIMITS IN AIR BY VOLUME

LEL : N/A **UEL:** N/A

EXTINGUISHING AGENTS: Using extinguishing media appropriate for surrounding fire

PERSONAL PROTECTIVE EQUIPMENT :

Standard industrial hygiene practices.

MATERIAL SAFETY DATA SHEET

CONTINUED: page 2

EVO-BOND

SECTION V - REACTIVITY:

STABILITY - Stable

HAZARDOUS DECOMPOSITION PRODUCTS - stable

INCOMPATIBILITY - No known materials which are incompatible

HAZARDOUS POLYMERISATION - Will not occur.

SECTION VI - HEALTH HAZARD INFORMATION:

HEALTH EFFECTS FROM OVER EXPOSURE

EYE CONTACT - Eye irritation, redness on contact

SKIN CONTACT - May cause irritation, dryness and dermatitis on prolonged contact

NASAL CONTACT - May cause irritation, dizziness, fatigue, nausea and headache

INGESTION - Can cause gastrointestinal irritation, nausea, vomiting and diarrhea

CARCINOGENICITY : NTP? – NO IARC MONOGRAPHS: -NO OSHA

REGULATED -NO

EMERGENCY FIRST AID INFORMATION:

EYE CONTACT - Flush eyes with water for at least 10 minutes

SKIN CONTACT - Wash affected areas with soap and water.

INHALATION - Move subject to fresh air, if breathing is difficult, give oxygen.

INGESTION - Give 2 glasses of water to drink to dilute. Consult a doctor.

DO NOT INDUCE VOMITING

SEE A DOCTOR IF DEEMED NECESSARY IN ALL CASES.

SECTION VII - SPILL OR LEAK HANDLING PROCEDURES:

Eliminate all ignition sources. Provide good ventilation, dike spill area and cover with inert and/or absorbent material (sand or earth) and remove to disposal container. Observe all relevant federal, state and local laws.

MATERIAL SAFETY DATA SHEET

CONTINUED: page 3

SECTION VIII - STORAGE AND HANDLING INFORMATION:

Store in a well ventilated area. Keep containers closed when not in use. Keep from freezing material may coagulate. Minimum recommended storage temperature is 1 degree Celsius. Keep away from excessive heat and open flame. Maximum recommended storage temperature is 49degrees Celsius.

The information contained herein is based on data considered accurate. However. No warranty is expressed or implied regarding the accuracy of this data or results to be obtained from the use thereof. Vendor assumes no responsibility for injury to Vendee or third person proximately caused by material if reasonable safety procedures are not adhered to as stipulated in the data sheets. Additionally, Vendor assumes no responsibility for injury to Vendee or third person proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, Vendee assumes the risk in the use of this material.

REGULATORY INFORMATION :

This product is not hazardous according to EEC directives 67/548/EEC and 99/45/EC

Australia Industrial Chemical Act (AUSTR) all ingredients in this preparation are listed in the Australian Inventory of Chemical Substances, AICS

Storage : 12 months from date of manufacture, stored under cover away from direct sunlight.

Application instructions and dilution rates :

Apply by low pressure spray equipment, brush / paint roller
Dilute as required.

Refer to distributors recommendations.



M. A. Total Build Ltd
149 Arch. Makarios III Avenue
3021 Limassol, Cyprus

info@totalbuild.com.cy
Tel: +357 99 121841
Fax: +357 25 381403